

# iridium PotsDOCK 9555



# iridium PotsDOCK 9555

**PotsDOCK 9555** is an intelligent compact docking station specifically designed for the Iridium 9555 satellite handset. **PotsDOCK** allows the 9555 handset to be used in a wide variety of applications using an intelligent RJ11/POTS connectivity that supports standard corded, cordless or DECT handsets, or alternatively interfaced with a PBX system.

**PotsDOCK** also has an in-built Bluetooth® module for voice and data connectivity along with an intelligent tracking and alert reporting system that can be easily configured to support periodic polling or emergency alert reporting.

The cleverly designed **PotsDOCK** cradle simply and securely docks the Iridium 9555 handset into place ready for use and fully integrates antenna, power and data connectivity into a single streamline unit.

The 9555 handset is easily inserted and removed by the press of a button on the top of the dock, making it very easy for use out of the dock at anytime.

**PotsDOCK** also supports the use of an optional compact Beam Privacy Handset that can be located next to the **PotsDOCK** for added convenience if required.



PotsDOCK 9555



GPS




ALERT



TRACKING



POTS /RJ11



Bluetooth®



USB DATA



PotsDOCK 9555 with optional Privacy Handset

## APPLICATIONS



In-building



Motor Homes /  
Recreational Vehicles



Emergency Services



Disaster Recovery

## KEY FEATURES AND BENEFITS

### POTSDOCK 9555 CRADLE

- Securely holds 9555 handset
- Robust design and construction
- Charges 9555 handset ready for use
- Integrated antenna connection
- Integrated USB connectivity

### POTS/RJ11

- Supports standard cordless & corded telephones (5 REN)
- RJ11 can be run 600m (2000 ft) from unit
- Corded, cordless or DECT handsets
- Easily integrated to PBX system
- Ring, busy & dial tones
- Superior voice quality

### TRACKING/GPS

- Tracking & alert monitoring capable
- Periodic position reports or remotely polled
- Triggered position status message
- In-built GPS engine
- Interfaces to Beam's LeoTRAK-Online
- Also compatible with other tracking applications

### PANIC/ALERTS

- Panic alert button in-built to cradle
- Option of additional wired alert buttons
- Interfaces to Beam's LeoTRAK-Online

### INTEGRATED BLUETOOTH®

- Bluetooth® in-built in cradle
- Supports Bluetooth® voice & data accessories

### IN-BUILT RINGER

- In-built ringer for enhanced ring indication

### VOICE, DATA, SMS, SBD

- Supports all Iridium voice, data, SMS & SBD services
- Access to prepaid, post paid & crew calling

### PRIVACY HANDSET

- Supports optional Beam privacy handset
- Auto sensing answer/hang-up intelligence

### INSTALLATION

- Supports 9 - 32V DC power input
- Flexible installation via universal mount, also suitable for wall mounting
- Supplied with 110 - 240V AC Plug pack
- Handset always charged ready for use

### QUALITY

- Professional industrial design
- 2 year peace of mind with a replacement guarantee
- 100% factory tested
- Full certified, Iridium, RoHS, CE, IEC60945

## TRACKING / ALERT MONITORING

PotsDOCK has an in-built GPS module that can provide simple tracking, monitoring and alert management in various land based applications within various types of vehicles or fixed site locations.

The GPS provides pinpoint accuracy and enables tracking worldwide. Tracking and alert messages can be sent via SMS or Short Burst Data, if provisioned on the handset.

PotsDOCK's tracking and alert messages can be simply sent to Beam's LeoTRAK-Online or any other tracking application, SMS or email address as required.

Tracking messages can be sent from the PotsDOCK via the following means;

1. Periodic position reporting, preset during configuration of the terminal
2. Upon an alert being activated via the Alert button on the cradle or connected alert button
3. A current location position can be sent at any time by pressing the Track button on the front of the PotsDOCK

Alert/Alarm messages can be activated on the PotsDOCK using the two button press on the front of the cradle or alternatively an additional alert button or other trigger can be connected to the unit. Once configured the alert system is always on and will generate an alert message to the preset destination once triggered. Alerts can be triggered to continually send until the alert is cleared either remotely or locally on the PotsDOCK unit.



## LEOTRAK-ONLINE GLOBAL TRACKING PORTAL

LeoTRAK-Online is Beam's own global web based alert monitoring and tracking application which for a small monthly fee per asset enables you to track, trace and monitor anywhere on earth through a simple to use web portal. For more information about LeoTRAK-Online and associated charges please visit [www.leotrakonline.com](http://www.leotrakonline.com)



# PotsDOCK 9555 TECHNICAL SPECIFICATIONS

## IRIDIUM NETWORK

9555 Handset	1616 - 1625 MHz
Compressed Data	10 - 12 kbps
Voice/Data Modulation	2.4 kbps

## I/O Alarm/Alert

Alert Button	In-built on PotsDOCK - 2 Key Press
1 x Alarm Loop	Bare Wire - "Normally Closed" Loop IN to OUT
Track	Up to 500m cable run/multi buttons Inbuilt - single key press

## PotsDOCK 9555 CRADLE

### Power Specifications

Power Input Voltage	9 - 32V DC, 2A max
---------------------	--------------------

### Power Consumption at 12V DC

Stand-by* - incl handset & RJ11	1.1W (90mA @ 12Vin)
Transmit - incl handset & RJ11	6W (0.5A @ 12Vin)

\* When battery charged

### GPS Module (internal)

Channels	14 tracking, 51 Channel Acquiring
Update Rate	1Hz
Accuracy	Position 2.5mCEP, Velocity 0.1m/s, Timing 300ns
Acquisition TTFF	Cold 29sec, Hot 1sec
Sensitivity	-161 dBm
Operational Limits	Altitude 18000m , Velocity 515m/s
Dynamics	4G

### Physical Specifications

	PotsDOCK	Packed
Dimensions - mm	200 x 75 x 65	325 x 140 x 88
Dimensions - inches	7.9 x 3.0 x 2.7	7.2 x 5.1 x 1.0
Weight - kg	0.32	1.3
Weight - lbs	0.7	2.86

### Environment Specifications

	Degrees °C	Degrees °F
Operating Range	-30 to +70	-22 to +158
Storage	-40 to +85	-40 to +185
Humidity	≤93% RH	

### Connectors/Interfaces

POTS/RJ11	RJ11 1/2-wire, complex or 600 Ω, 5REN, 600m adjustable dial/busy tones/frequency, adaptive Z
Iridium - Antenna	Fixed Cable to TNC-Female
GPS-Antenna	Fixed Cable to SMA-Female
9-32 V DC	4-way microFit (AC/DC adator, or DC lead)
Privacy Handset Port	4 pole 3.5mm jack
Data Port	USB Mini Base of Dock
Bluetooth® Voice / Data	Inbuilt module/antenna, class 1 (up to 300m) Bluetooth® system 2.0v+EDR, CE and FCC

### Buttons/LEDs

	LED
Bluetooth®	Blue/Orange
Alert	Red/Orange
Mute/Ringer	Red
Backlight	White LED
Handset Release	Top of Cradle, No LED

### Certifications

Iridium
Electrical Safety
EMC Compliance
CE Compliance
RoHS
C Tick
<b>Independent</b> Aeronautical certification <b>MUST</b> be gained prior to installation

## ACCESSORIES

RST702	Dual Mode Iridium/GPS Mast Mount Antenna
RST705	Dual Mode Iridium/GPS Magnetic Mount with 6m of cable for each attached
RST710	Iridium Mast Mount Antenna
RST715	Iridium Magnetic Mount Antenna incl 5m cable
RST725	Bluetooth® Headset incl car charger
RST755	Beam Privacy Handset
RST932	6m/ 18ft Iridium Cable Kit
RST933	12m/36ft Iridium Cable Kit
RST942	6m/ 18ft GPS Cable
RST923	12m/36ft GPS Cable

## KIT CONTENTS

Beam PotsDOCK Cradle  
 Universal Mounting Bracket (RAM)  
 110 - 240V AC Plug Pack  
 9 - 32V DC Power Cable  
 User Manual  
 Quick Start Guide

## BUNDLE PACKS AVAILABLE \*

Voice Bundle  
 Voice and Tracking Bundle

\* See your Beam Approved Reseller

APPROVED BEAM RESELLER:



www.bluecosmo.com  
 customercare@bluecosmo.com  
 phone: +1 206 329 1947  
 toll free: +1 877 258 3496

PHONE: +61 3 8588 4500 FAX: +61 3 9560 9055  
 EMAIL: info@beamcommunications.com  
 WEB: www.beamcommunications.com



AFRICA | ASIA | AUSTRALIA | EUROPE | MIDDLE EAST | NORTH AMERICA | SOUTH AMERICA